

PW40 - Classic Ear Muffs

Collection: Ear Muffs

Range: Hearing Protection

Materials: ABS, Polycarbonate, PVC

Outer Carton: 48

Product information

Lightweight and robust, the PW40 is suitable for all day comfort. Excellent attenuation rate. Metal-free design.

Ear Muffs

Portwest Hearing protection range includes PPE with different level sound attenuation, to be adapted to various working environments giving the correct protection from dangerous noise, without isolating the workers. New models and colors for earmuffs allow a personalized choice. An updated range of earplugs complete our competitive and performing offer.

Hearing Protection

Hearing problems occur when you are exposed to hazardous working conditions without wearing the correct protective equipment.

Standards

ANSI S3.19 (NRR 22dB)

EN 352-1 (SNR 27dB)



Features

- Ultra light and compact ear muff
- Adjustable length for a secure and comfortable fit
- Excellent attenuation rate
- Metal Detector Friendly: Non-Magnetic - Nickel and Ferrous free
- Retail bag which aids presentation for retail sales
- Individually packed for vending machines
- Classic design ear muff
- Metal free
- Light and robust
- SNR 27dB attenuation level
- 100% Metal free

PW40 - Classic Ear Muffs**Commodity Code: 3926909790****Test House**

BSI Group The Netherlands B.V. (Notified Body No.: NB: 2797)
John M. Keynesplein 9
, The Netherlands
Cert No: CE 800492

Michael & Associates, Inc. (Notified Body No.:)
2766 W. College Ave Suite 1
PA 16801, United States

Carton Dimensions/Weight

Item	Colour	Len	Wid	Hgt	Weight(Kg)	Cubic(m ³)	EAN13	DUN14
PW40RER	Red	60.0	40.0	40.0	0.1720	0.0960	5036108134656	15036108636201

PERFORMANCES - SOUND ATTENUATION - EN 352-1:2002

PW40/PS40		SNR 27.6dB				H:29.2 M:25.4 L:17.9			
A	Frequency (Hz)	63	125	250	500	1000	2000	4000	8000
B	Mean Attenuation (dB)	18.1	15.0	18.3	26.8	37.5	29.5	35.8	36.1
C	Standard Deviation (dB)	4.1	2.7	3.3	2.0	4.1	2.9	3.3	5.8
D	Assumed Protection (dB)	14.0	12.3	15.0	24.8	33.4	26.6	32.5	30.3

PW40RER